

MODEL 4600XL TRACK WOOD HOG

- An aggressive, productive track grinder from the leading manufacturer of industrial grade grinding equipment.
- Process clearing debris, yard waste, storm debris and other mixed woody feedstocks into saleable products.
- Backed by a world class parts & service support team.
- Long lasting, durable machine that holds its value.



IQAN SYSTEM

Automatically adjusts feed rates, monitors pressures and feed wheel position to maximize production and engine efficiency.



HAMMERMILL

Laser-cut upturn rotor, factory balanced with forged hammers offer unsurpassed durability and smooth operation.



FEED SYSTEM

Internal planetary drive on feed wheel with no chains and sprockets means lower maintenance, more torque and better durability.



TRACK AND DRIVE

325L Caterpillar undercarriage with 600mm double grouser shoes. 11.6 PSI ground pressure and 1.4-2.4 MPH ground speed with clearance of 20"



SPECIFICATIONS

GENERAL

Length (transport).....	45'
Length (operating).....	45'11"
Height	12'
Width	11'3"
Gross weight	86,260 lbs.
Engine.....	CAT or Cummins
Horsepower.....	630 HP to 1050 HP
Fuel capacity (tank)	300 gallons
Hydraulic oil capacity.....	267 gallons
IQan System	
Wireless radio remote control	

INFEED SYSTEM

60" x 46" infeed opening
 9.3 cubic yard infeed hopper
 12'6" x 60 3/8" live floor with 4-strand WDH 120 chain
 (1) horizontal feed wheel with internal drive, 33" diameter x 61 3/8" wide

HAMMERMILL AND GRATES

36" diameter x 61 3/8" hammermill with 36" tip swing
 25 1/2" diameter rotors, (18) 1 3/8" thick rotor plates on 8 3/8" diameter rotor shaft with 5 3/16" Dodge bearings, (8) 2 1/4" hammer retaining rods (8) 2" thick-balanced T-1 forged fixed teeth insert holders equipped with (18) 2 1/2" wide double-edged replaceable carbide teeth inserts and eighteen rakers. Three sections of 1" thick wear form steel heavy duty hexagon grates.

DISCHARGE SYSTEM

Two hydraulically driven aggregate grade belt conveyors
 One 48" belly belt on to a 36" wide stacking conveyor with hydraulic fold for transport
 Stacking height 11'

OPTIONS

Caterpillar 325EL undercarriage • Variety of screen sizes available • Hydraulic reversing fan
 • Wireless data connection for IQan System • Hydraulic rod pusher • Various hammer patterns • Extended stacking conveyor • 11-HP air compressor • Magnetized end pulley



800-831-0042 • 989-866-2381
www.morbark.com