

# MODEL 6600 WOOD HOG

- An aggressive, productive grinder from the leading manufacturer of industrial grade grinding equipment.
- Process clearing debris, yard waste, storm debris and other mixed woody feedstocks into saleable products.
- Backed by a world class parts & service support team.
- Long lasting, durable machine that holds its value.
- Proven drive line protection system that protects against catastrophic damage from contaminants.
- Built in a quality-driven factory by highly experienced personnel.



## IQAN SYSTEM

Automatically adjusts feed rates, monitors pressures and feed wheel position to maximize production and engine efficiency.



## HAMMERMILL

Laser-cut upturn rotors, factory balanced with forged hammers offer unsurpassed durability and smooth operation.



## FEED SYSTEM

Internal planetary drive on feed wheel with no chains and sprockets means lower maintenance, more torque and better durability.



## INFEEED BED

WHD 120 infeed chain is heavy duty, rugged and long lasting.



## SPECIFICATIONS

### GENERAL

Length (transport).....44'6"  
 Length (operating).....67'9"  
 Height .....13' 4"  
 Width .....10' 2"  
 Gross weight .....89,360 lbs.  
 Axle weight.....59,160 lbs.  
 Tongue weight .....26,000 lbs.  
 Engine.....CAT or Cummins  
 Horsepower..... 800 HP to 1,200 HP  
 Fuel capacity (tank) .....430 gallons  
 Hydraulic oil capacity.....238 gallons  
 Iqan System • Wireless radio remote control • Triple axle trailer (with air ride suspension) • Adjustable fifth wheel pin • 11 HP air compressor

### INFEEED SYSTEM

66" x 50" infeed opening  
 13.8 cubic yard infeed hopper  
 17'4" x 5'4" live floor with 5-strand WHD 120 chain  
 (1) horizontal feed wheel with dual hydraulic drive,  
 36" x 64<sup>3</sup>/<sub>4</sub>"

### HAMMERMILL AND GRATES

42" diameter x 67" hammermill with 42" tip swing  
 28" diameter rotors, (18) 1<sup>3</sup>/<sub>8</sub>" thick rotor plates on 8<sup>1</sup>/<sub>4</sub>" diameter rotor shaft with 5<sup>3</sup>/<sub>16</sub>"  
 Dodge bearings, (8) 2<sup>1</sup>/<sub>2</sub>" hammer retaining rods, (30) 2<sup>1</sup>/<sub>4</sub>" thick balanced T-1 steel fixed teeth insert holders equipped with (30) 3" wide double edged replaceable carbide teeth inserts. Four sections of 1" thick wear form steel heavy-duty hexagon grates

### DISCHARGE SYSTEM

Two hydraulically driven aggregate grade belt conveyors  
 One 48" belly belt on to 40" wide stacking conveyor with hydraulic fold for transport  
 Stacking height 18'6"

### OPTIONS

• Magnetized end pulley • Variety of grate sizes available • Hydraulic reversing fan • Leaf spring suspension • Wireless data connection for Iqan System



800-831-0042 • 989-866-2381  
[www.morbark.com](http://www.morbark.com)