

MODEL 950 TUB GRINDER

- A compact, easy to haul tub grinder for lower volume applications.
- Process yard waste, pallets and other mixed woody feedstocks into saleable products.
- Backed by a world class parts & service support team.
- Long lasting, durable machine that holds its value.
- Proven drive line protection system that protects against catastrophic damage from contaminants.
- Built in a quality-driven factory by highly experienced personnel.



HAMMERMILL

Laser-cut, factory balanced hammermills with forged hammers offer unsurpassed durability and smooth operation.



HYDRAULIC AUGERS

Quickly remove product from beneath the mill. During material surges, pressure sensors on the auger system automatically slow tub rotation to prevent plugging.



TORQUE LIMITER

The full breakaway torque limiter system protects the engine and clutch against shock and overload without stalling the engine.



TUB TILT

Provides easy access to grates and anvil for routine maintenance.



SPECIFICATIONS

GENERAL

Length (transport).....	22'
Length (operating).....	29'5"
Height	12'5"
Width	8' 6"
Gross weight	12,360 lbs.
Axle weight.....	11,600 lbs.
Tongue weight	760 lbs.
Engine.....	CAT, Cummins, or John Deere
Horsepower.....	173 HP to 213 HP
Fuel capacity (tank)	59 gallons
Hydraulic oil capacity.....	50 gallons
Wireless radio remote control	

TUB

Hydraulic tilt
 8'4" diameter tub opening, 6'6" diameter at inside base and 44" deep
 Wall constructed of 3/16" reinforced steel plate, floor constructed of 1/4" thick T-1 wear-resistant steel
 Tub supported by five rubber guide rolls carried on a 1 1/2" diameter chrome shaft
 Hydraulic forward and reverse with tub sensor
 Safety shut down system
 Tub cover for debris containment

HAMMERMILL AND SCREENS

23" x 32 1/2" hammermill opening
 16" diameter x 30 1/2" long rotor with eight 1 1/4" heat-treated hammer retaining rods mounted on an 4 1/2" diameter rotor shaft
 22 1/2" diameter tip swing
 Equipped with (24) 1 1/4" thick balanced heat-treated,

hard-surfaced fixed hammers with replaceable inserts
 3/4" thick T-1 steel heavy-duty split screens
 Wear plate and screen area 1,612 sq. inches

DISCHARGE SYSTEM

Two 12" diameter discharge augers
 28" wide x 12' long conveyor with hydraulic fold for transport

OPTIONS

Magnetized end pulley with collecting slide tray for ferrous metal removal
 Six function wireless remote control
 Fifth wheel towing arrangement
 11 HP auxiliary air compressor
 28" wide x 15' long folding discharge conveyor
 Swing hammers



800-831-0042 • 989-866-2381
www.morbark.com