

PREDATOR SHREDDER

- Easy access to hydraulics making maintenance easy and fast and minimizing downtime.
- Heavy-duty breaker beam allows sizing of the end product.
- Powerful cross belt magnet removes heavy ferrous metal contaminants from discharge stream/end product.
- Dual belt discharge system allows for increased discharge capacity.
- Dual rotors provide the ability to shred a variety a materials without wrapping around a single rotor.
- Discharge conveyor folds hydraulically for transport.



DUAL ROTORS

Each hooked star has a double edged tooth staggered across the star for 100 percent coverage for grabbing and ripping in both directions.



DRIVE SYSTEM

Two 144:1 reducing transmissions produce a million inch pounds of torque to each rotor.



IQAN SYSTEM

Boost production levels and substantially minimize downtime with this smart system uniquely programmed to Morbark machines.



CAB & LOADER

Also available with a cab and loader eliminating the need for additional support equipment.



SPECIFICATIONS

PREDATOR STANDARD

Operating Length..... 38'6"
 Transport Length..... 30'6"
 Operating Height 11'11"
 Transport Height..... 8'10"
 Width 8'2-1/2"
 Gross Weight 44,000 lbs.
 Horsepower Range 335-450

Gross Weight..... 61,000 lbs.
 Horsepower Range..... 335-450

PREDATOR WITH CAB/LOADER

Operating Length..... 58'
 Transport Length 39'
 Operating Height 17'
 Transport Height..... 13'6"
 Width 11'1"
 Gross Weight..... 76,020 lbs.
 Horsepower (CAT C-13) 440;
 (CAT C4.4) 114
 Telescoping Cab raises 22"

PREDATOR 5th WHEEL FRAME

Operating Length..... 58'
 Transport Length 39'
 Operating Height 17'
 Transport Height..... 13'6"
 Width 11'1"

FEED HOPPER

76" x 98" fixed section, 98" x 139" pivoting section which raises hydraulically to a 45 degree angle

OPTIONS

Electric power
 Fifth wheel frame
 Cab & Loader
 Rotating Cab



800-831-0042 • 989-866-2381
 www.morbark.com