

20/36 TRACK CHIPPER

OPTIONS

- Halogen light package
- Espar heating system for cold weather start
- Self-contained 5 HP split air compressor
- Skidder-style blade
- Electronic RPM sensor

FEATURES

- Pressurized water system
- Tool box



UNDERCARRIAGE
CAT 312B undercarriage provides 18" ground clearance, while an optional skidder-style blade stabilizes the unit on steep grades.



OPERATOR'S CAB
All weather cab provides optimal comfort during operation.



LOADER
The Morbark 150 knuckleboom loader allows for the chipping of whole trees and a variety of wood waste.



INFEED BED
Large infeed opening easily accepts tangled brush, limbs and logs.



SPECIFICATIONS

Length	20'6"
Height	11'6"
Width	9'6"
Gross weight	28,320 lbs.
Engine.....	CAT, Cummins or John Deere
Horsepower.....	325 - 400 HP
Fuel capacity (tank)	115 gallons
Hydraulic oil capacity.....	102 gallons
Chipping capacity.....	16" diameter
Brakes	spring applied hydraulic release parking brake

CAB AND LOADER

Enclosed weatherized operator's cab with joystick controls, 4-way adjustable seat, and combination air conditioner/heater
Morbark 150 hydraulic knuckleboom loader, 180° swing and 360° continuous by-pass grapple

INFEED SYSTEM

Infeed opening - 21" x 26"
19" CAT chain feed table
One top feed wheel, 20" diameter, mounted on a yoke assembly

DISCHARGE SYSTEM

Chips thrown by centrifugal force with fan impeller system
180° swivel chip discharge spout with deflector

CHIPPER ASSEMBLY

Drum diameter.....	36"
Drum width	20"
Knife pockets (4)	9 1/4" x 10 1/2" x 8"
Chipper knives (4)	10 1/2" x 5" x 1/2" thick, Babbit style, resharpenable and made of A-8 steel
Drum speed	1,250 RPM
Feed drive.....	hydraulic

TRACK AND DRIVE

Caterpillar.....	312B
Shoes.....	500mm, triple grouser
Ground clearance.....	18"
Ground speed.....	1.7 - 2.8 MPH
Ground pressure	6.0 - 6.5 PSI
Hydrostatic transmission with double foot pedal controls	



800-831-0042 • 989-866-2381
www.morbark.com