

20/36 WHOLE TREE CHIPPER

OPTIONS

- Halogen light package
- Espar heating system for cold weather start
- 5 HP air compressor
- Tool box
- NCL available
- 5' infeed extension



OPERATOR'S CAB

All weather cab provides optimal comfort during operation.



DISCHARGE

Direct flow discharge can be equipped with optional assist blower to increase capacity when chipping fine brush and other light materials.



INFEED OPENING

Oversized infeed opening easily accepts tangled brush, limbs and logs.



LOADER

The Morbark 150 knuckleboom loader allows for the chipping of whole trees and a variety of wood waste.



SPECIFICATIONS

GENERAL

Length	27'
Height	10'3"
Width	8'6"
Gross weight	19,900 lbs.
Tongue weight	3,000 lbs.
Axle weight.....	16,900 lbs.
Tandem axle	20,000 lbs. Tor-Flex suspension
Engine.....	CAT, Cummins or John Deere
Horsepower.....	250 - 350 HP
Fuel capacity (tank)	115 gallons
Hydraulic oil capacity.....	102 gallons
Chipping capacity	16"
Tires (4).....	LT245/75R 16 ply radial
Brakes	electric

CAB AND LOADER

Enclosed weatherized operator's cab with joystick controls, 4-way adjustable seat, and combination air conditioner/heater
 Morbark 150 hydraulic knuckleboom loader, 14' extended boom, 180° swing and 360° continuous by-pass grapple
 Lift capacity of 2,000 lbs. at 10'

INFEED SYSTEM

Infeed opening - 21" x 26"
 19" CAT chain feed table
 One top feed wheel, 20" diameter, mounted on a yoke assembly

CHIPPER ASSEMBLY

Drum diameter.....	36"
Drum width	20"
Knife pockets (4)	9 1/4" x 10 1/2" x 8"
Chipper knives (4)	10 1/2" x 4 3/16" x 1 1/2" thick
Knives are Babbit style	
Drum speed	1,250 RPM
Feed drive.....	hydraulic

DISCHARGE SYSTEM

Chips thrown by centrifugal force with fan impeller system
 180° swivel chip discharge spout with deflector



800-831-0042 • 989-866-2381
www.morbark.com