

Model 22 Chiparvestor (RXL and NCL)

OPTIONS

- Reversing fan
- Choice of PT Tech or Twin Disc hydraulic clutch
- Four-knife chipper disc
- Electronic RPM sensor
- Espar heating system for cold weather start
- 11-HP air compressor
- Discharge spout extension (RXL)
- Electric power option



OPERATOR'S CAB (RXL)

Roomy, climate-controlled cabs are equipped with comfortable seats, joystick controls and full instrumentation.



CHIPPER DISC

Each disc is fabricated from plate steel and put through ultrasonic testing. Material certification is issued for each disc, which provides the best chipper disc in the industry.



FEED SYSTEM (NCL)

Powerful multi-wheel feed system provides positive feed of logs and tops for excellent chip quality.



CHIP QUALITY

Units produce quality chips even in non-merchantable and juvenile timber.



SPECIFICATIONS

GENERAL - MODEL 22 RXL

(with cab and loader)

| | |
|-----------------------------|-----------------------|
| Length | 41' |
| Height | 13'6" |
| Width | 11' |
| Gross weight | 81,300 lbs. |
| Horsepower | up to 1,050 HP |
| Engine..... | CAT or Cummins |
| Tandem axle trailer | 50,000 lb. suspension |
| Fuel tank capacity | 400 gallon |
| Hydraulic oil capacity..... | 300 gallon |

GENERAL - MODEL 22 NCL

(without cab and loader)

| | |
|--------------|-------|
| Length | 27' |
| Height | 13'4" |

| | |
|-----------------------------------|-----------------------|
| Width | 10'8" |
| Gross weight | 52,000 lbs. |
| Horsepower..... | up to 875 HP |
| Engine..... | CAT or Cummins |
| Tandem axle trailer | 50,000 lb. suspension |
| Fuel tank capacity (NCL) | 200 gallon |
| Hydraulic oil capacity (NCL)..... | 200 gallon |

DISCHARGE SYSTEM

Dirt separator with deflector
Hydraulic swivel/telescoping discharge spout

CHIPPER

22" diameter chipping capacity
75" diameter three-knife chipper disc with LH rotation
Chip sizes: 5/8", 3/4", 7/8", 1", 1-1/4", 2"
Hydraulic chipper hood for easy knife access

FEED SYSTEM

Infeed system consists of three hydraulic feed wheels (RXL)
Infeed system consists of four hydraulic feed wheels (NCL)
30" x 10' CAT chain infeed bed (RXL)

CAB AND LOADER (RXL)

Enclosed weatherized operator's cab is mounted on rubber shock absorbers with combination air conditioner/heater
Tilts hydraulically for transport
Six-way adjustable seat and joystick controls
Morbark 1000 knuckleboom loader, 25' reach, 210° swing and by-pass grapple
Lift capacity of 20,000 lbs. at 10'



800-831-0042 • 989-866-2381
www.morbark.com