

# Morbark Model 30 Chiparvestor

## OPTIONS

- Reversing fan
- Choice of PT Tech hydraulic clutch, Twin Disc hydraulic clutch or Twin Disc dry clutch
- Four-knife chipper disc
- Electronic RPM sensor
- Espar heating system for cold weather start
- 11-HP air compressor
- Tri-axle
- Electric power option
- Discharge spout extension (RXL)



**MODEL 30 NCL**

Produce clean chips by positioning an NCL behind a stand-alone debarker or feed with an auxiliary loader.



**CHIPPER DISC**

Each disc is fabricated from plate steel and put through ultrasonic testing. Material certification is issued for each disc, which provides the best chipper disc in the industry.



**FEED SYSTEM**

Powerful multi-wheel feed system provides positive feed of logs and tops for excellent chip quality.



**CHIP QUALITY**

Units produce quality chips even in non-merchantable and juvenile timber.



## SPECIFICATIONS

### GENERAL - MODEL 30 RXL (with cab and loader)

Length ..... 41'  
 Height ..... 13'6"  
 Width ..... 11'  
 Gross weight ..... 82,000 lbs.  
 Horsepower ..... up to 1050 HP  
 Engine ..... CAT or Cummins  
 Tandem axle trailer ..... 50,000 lb. suspension  
 Fuel tank capacity ..... 400 gallon  
 Hydraulic oil capacity ..... 300 gallon

### GENERAL - MODEL 30 NCL (without cab and loader)

Length ..... 32'  
 Height ..... 13'4"  
 Width ..... 10'4"  
 Gross weight ..... 58,000 lbs.

Horsepower ..... up to 875 HP  
 Engine ..... CAT or Cummins  
 Tandem axle trailer ..... 50,000 lb. suspension  
 Fuel tank capacity ..... 300 gallon  
 Hydraulic oil capacity ..... 200 gallon

### CHIPPER

30" diameter chipping capacity  
 83" diameter three-knife chipper disc with LH rotation  
 Chipper disc is 5" thick and weighs 8000 lbs.  
 Chip sizes: 5/8", 3/4", 7/8", 1", 1-1/4", 2"  
 Hydraulic chipper hood for easy knife access

### FEED SYSTEM

30" x 10' CAT chain infeed bed (RXL)  
 Three wheel hydraulic feed system (RXL)  
 Two 13" x 25-3/4" side feed wheels and one 22-1/4" x 68" top feed wheel  
 Four wheel hydraulic feed system (NCL)

### DISCHARGE SYSTEM

Dirt separator with deflector and quick change  
 Hydraulic swivel/telescoping discharge spout

### CAB AND LOADER (RXL)

Enclosed weatherized operator's cab is mounted on rubber shock absorbers with combination air conditioner/heater  
 Tilts hydraulically for transport  
 Six-way adjustable seat and joystick controls  
 Morbark 1000 knuckleboom loader, 25' reach, 210° swing and by-pass grapple  
 Lift capacity of 20,000 lbs. at 10'

### REMOTE CONTROL (NCL)

Wireless remote control with tethered backup.



800-831-0042 • 989-866-2381  
[www.morbark.com](http://www.morbark.com)