

628 DEBARKER

FEATURES

- 20' trough-type infeed conveyor with WD-110 chain and hydraulic drive.
- 20' trough-type outfeed conveyor with WD-110 chain, hydraulic drive and outfeed dump.
- Dumps either right or left.
- Front yoke set at 10° or 16°.
- Hydraulic shoe for bark removal depth.
- Hydraulic top wheel is adjustable & backwheel is fixed.
- Table lock assembly.



SPECIFICATIONS

GENERAL

Length (includes infeed and outfeed sections).....	44'
Width (debarker section).....	11'5"
Height (debarker section).....	10'3"
Weight (debarker section).....	8,000 lbs.
Infeed weight (standard).....	5,000 lbs.
Outfeed weight (standard).....	4,500 lbs.
Handles Material.....	6" - 28" diameter
Production.....	Up to 60 lineal feet/minute
Engine type.....	Electric
Horsepower.....	50 HP, 75 HP or 100HP
Auxiliary Power.....	50 HP

OPTIONS

Trough conveyors constructed from 5/8" panning in lieu of 1/2"
 13" track type chain in lieu of WD-110
 3/4" UHMW Duralite wear strip mounted in conveyor pan for chain to ride on
 Elevated operator's console, complete with access ladder, seat, and hose hook-up
 All weather operators' cab. Cab is 54" wide x 58" long x 6'8" tall and includes two (2) side windows for cross ventilation
 Side mounted combination air conditioner/heater unit for cab enclosure
 Hoses are provided to position operator's console approximately 4' from the debarker center section. Cab positions requiring longer hoses are available.
 Longer outfeed or infeed trough

Auxiliary Hydraulic Pumps operated off 50-HP Electric Motor (motor not included) to facilitate independent drive on infeed and outfeed conveyors and to operate additional material handling equipment (note: this makes all hydraulics separate from cutterhead)
 16° Yoke setting for high speed debarking up to 16" diameter logs

KICKER OPTIONS

4-arm manual kickers with dual cylinders
 Additional 3-arm manual kickers



50 years of experience...



worth its weight in gold.

800-831-0042 • 989-866-2381
www.morbark.com