

BARN SWEEP CONVEYOR

OPTIONAL EQUIPMENT

- Length - per foot
- Hydraulic drive in lieu of standard



SPECIFICATIONS

GENERAL

5' - 150' level, 5'-10' upright barn sweep style conveyor
5/8" oval link chain with flites on 2' centers (standard), other options available
Constructed from 10 gauge formed steel pan and 5" x 5" square tubing
2-7/16" head shaft, tail shaft and idler shaft
Heavy duty tubular steel leg package available with optional discharge heights
Rexnord gear reducer 25 to 1 reduction
Chain speed approximately 30 FPM
3 HP, 1800 RPM electric motor
Ratchet type chain tensioner

STANDARD EQUIPMENT

25' level, 30' upright barn sweep style conveyor
5/8" oval link chain with flites on 2' centers
Constructed from 10 gauge formed steel pan and 5" x 5" square tubing
2-7/16" head shaft, tail shaft, and idler shaft
heavy duty tubular steel leg package with discharge height of 15 foot
Rexnord gear reducer 25 to 1 reduction
Chain speed approximately 30 FPM
3 HP, 1800 RPM electric motor
Ratchet type chain tensioner



50 years of experience...



worth its weight in gold.

800-831-0042 • 989-866-2381
www.morbark.com