

# TYPHOON 20 BRUSH CHIPPER

## BENEFITS

- TorqMax plus dual feed wheel compression system generates 9,935 lb/ft of combined hydraulic feed wheel pulling force
- 50% more chipping capacity than comparable 4-knife chipper
- 63.9ci displacement top and bottom feed wheel motors with 64% more top feed wheel torque than the Hurricane 18
- Ideal unit for: Lot and land clearing, bio-mass production, contractors and large tree services



**TORQMAX FEED WHEEL**  
TorqMax Plus Top Feed Wheel  
Compression System with 2:1 torque  
amplification



**DRUM/AIR IMPELLER SYSTEM**  
36" diameter, 6-knife staggered pocket  
drum with twin, 4-blade air impeller  
system



**REVERSING AUTOFEED**  
Reversing Automatic Feed System  
reduces wear and increases knife life



**HYDRAULIC DOWNFORCE**  
Variable Force Hydraulic Down  
Pressure System creates 450 lbs. of  
perpetual down pressure



## SPECIFICATIONS

### GENERAL

Chipping capacity .....	20"
Length .....	19'1"
Height .....	9'2"
Width .....	8'5 1/2"
Gross weight .....	13,900 lbs.
Suspension .....	(2) 10,000 lb. torsion
Infeed opening.....	.65" wide x 38" high
Throat opening .....	.28" wide x 20 3/8" high
Drum .....	28 1/2" wide x 36" diameter
Engine.....	CAT, John Deere or Perkins
Horsepower.....	250 - 325 HP
Fuel capacity (tank) .....	62 gallons
Hydraulic oil capacity.....	40 gallons
Frame.....	2" x 8" tubular steel
Tires .....	(4) 235/75R x 17.5"
Hitch.....	3" Lunet

### EQUIPMENT HIGHLIGHTS

2" x 8", fully boxed, extended steel frame with 2" x 6" infeed frame extensions  
Bearing style pivot system contours the drum radius, increases down pressure efficiency and reduces dead space.  
Six pocket staggered pocket drum with (6) 9 1/2" long chipper knives allowing (3) full cuts per revolution  
Patent pending variable force hydraulic down pressure system with 450 lbs. of perpetual down pressure  
Straight flow-through infeed design allows smooth transition between feed wheel and chipping drum

### ADDITIONAL FEATURES

1600 lb. of yoke down pressure at valve handle  
20,000 lb. tandem axle suspension  
8" infeed wall radius permits seamless material flow from the infeed to feed wheels  
Twin, 4-blade, integrated air impeller system with perforated drum slides

### OPTIONS

Mor-Lift model 150M knuckleboom loader  
Heavy-duty winch package with rope or steel cable  
Hydraulic dual rear stabilizers  
Wireless remote control  
Aluminum diamond plate fenders  
Special color paint  
Custom logo packages



800-831-0042 • 989-866-2381  
www.morbark.com