

# TYPHOON 20 WCL BRUSH CHIPPER

## BENEFITS

- TorqMax Plus Top Feed Wheel Compression System generates 9,935 lb/ft of hydraulic feed wheel pulling force
- 50% more chipping capacity than comparable 4-knife chipper
- 63.9ci displacement top and bottom feed wheels motors with 48% more top feed wheel torque than the Hurricane 18
- Ideal unit for: Lot and land clearing, bio-mass production, contractors and large tree services



### OPERATOR SEAT

Morbark's exclusive operator's seat and platform provides a 270° birds eye view of the chipping operation



### LOADER

Mor-Lift Model 150M Knuckleboom Loader provides a 14' extended boom reach and 2680lb lift at a 10' reach



### GRAPPLE

Model 649 continuous rotation, by-pass grapple with 6" closed tine diameter and 49 9/16" tine opening



**TURNTABLE/PEDESTAL**  
Pedestal mount features a heavy-duty, 23" diameter, turntable bearing and 59.9ci turn motor



## SPECIFICATIONS

### GENERAL

Chipping capacity .....	20"
Length .....	21'4"
Height .....	11'3"
Width .....	7'8"
Gross weight .....	17,500 lbs.
Suspension .....	(2) 10,000 lb. torsion
Infeed opening.....	41" wide x 67" high
Throat opening .....	28" wide x 20 <sup>3</sup> / <sub>8</sub> " high
Drum .....	28 <sup>1</sup> / <sub>2</sub> " wide x 36" diameter
Engine.....	CAT or John Deere
Horsepower.....	325 HP
Fuel capacity (tank) .....	62 gallons
Hydraulic oil capacity.....	40 gallons
Frame.....	2" x 8" tubular steel
Tires.....	(4) 235/75R x 17.5"
Hitch.....	3" lunet

### EQUIPMENT HIGHLIGHTS

Mor-Lift model 150M knuckleboom loader with 14' extended boom reach and 360°, continuous rotation, by-pass grapple  
Exclusive operator's seat and platform with 270° birds of view of the chipping operation  
Model 649 continuous rotation, by-pass grapple with 6" closed tine diameter, 49 9/16" tine opening and 3" welded cylinder  
2,680 lbs. extended boom lift capacity at 10'  
Pedestal mount features a heavy-duty, 23" turntable bearing with 59.9ci turntable motor  
Heavy-duty, 3" welded main boom cylinder and 3.5" jib boom cylinder  
Hood safety switch prohibits the engine from starting when the hood pin is removed

### ADDITIONAL FEATURES

Hydraulic front and dual rear stabilizers  
Hydraulic swivel discharge  
20,000 lb. tandem axle suspension  
Integrated loader carriage for ease of transport  
2" x 8" fully boxed, extended steel frame with 2" x 6" infeed frame extensions

### OPTIONS

Ground mounted operator's controls  
Winch package with rope or steel cable  
Air braking axles  
Caterpillar joystick controls  
Aluminum diamond plate fenders  
Special color paint  
Custom logo packages



50 years of experience...



worth its weight in gold.

800-831-0042 • 989-866-2381  
www.morbark.com