

# FTX 148-L



**Track Carrier**  
**The Ultimate Combination Of**  
**Compact Power & Reach**



# Technical Specifications

GENERAL	FTX148-L
Weight of tractor only	13,360 lbs.
Weight of tractor with BH85 Bullhog®	16,300 lbs.
Length of tractor with Quick Attach Plate	164"
Length of tractor with BH85 Bullhog®	208"
Height Overall	99"
Width At Tracks (Cross Link Track)	72"
Width Overall with BH85	85"
Travel Speed	1-7 mph
ENGINE	
Make	Caterpillar
Model	C 4.4
Number of Cylinders	4
Horsepower	142
Rated Torque @ RPM	405 ft. lbs. @ 1600
Cooling	Water Cooled
Fuel Tank	46 gal.
Air Cleaner	Dual Element Dry Type
HYDRAULIC SYSTEM *Fecon Power Management®	
System Pressure	6000 psi
High Flow	61 gpm
Low Flow	26 gpm
Hydraulic Reservoir	26 gallons
UNDERCARRIAGE	
Type	Steel Cross Link
Track Width	18"
Track Gauge	54"
Ground Pressure (Cross Link Track)	4.1 psi
Ground Clearance	14"



The new FTX148-L offers both big machine performance and unparalleled operator comfort in a compact utility size. The FTX148-L provides the right combination of purpose built mulching tractor and versatile multifunction carrier.

Capitalize on almost twice the performance of a typical skidsteer mulcher while being only slightly larger in size for transportability, tight work spaces, and low ground pressure. Achieve more revenue per day with the FTX148-L, from Fecon.

## FEATURES

- Ergonomically designed cab with side door entry
- Suspension Seat
- Loader arms for versatile performance
- Suspended undercarriage
- Excellent serviceability access
- Fecon Power Management®
- Quick Attach Coupler for Approved Attachments
- Reversing Engine Fan

## APPLICATIONS

- Right Of Way Clearing
- Agricultural Preparation and Land Development
- Park Trails and Maintenance
- Orchard Clean-up and Removal
- Prairie and Wetland Restoration
- Wildfire Urban Interface

## ACCESSORIES

- **Bull Hog® Mulcher** - Mulch brush, trees and stumps down to ground level quickly, safely and at the lowest possible cost.
- **Standard Winch** - Excellent for pulling machines out of difficult situations and skidding.
- **Front Grapple** - Transport and place landscape materials, tree removal, moving debris, rock and brush piles.

- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Safety Is The Responsibility Of The Operator.
- Always insure that your carrier manufacturers safety features, including Falling Object Protection, and Roll-Over Protection meet your job safety requirements.
- Specifications subject to change without notice.
- LEXAN® is a registered trademark of General Electric Company.

GSA GS-30F-0019S



7/08

www.fecon.com  
E-Mail: sales@fecon.com



Lebanon, Ohio  
Toll Free: 800.528.3113