



FTX440

Crawler Mulcher

Maximizing Productivity
and Uptime In The Woods



Technical Specifications

SPECIFICATIONS	
Engine	440HP Caterpillar® C13 diesel engine with auto-reversing radiator fan
Mulcher Drive	PTO with fluid coupler protection
Overall Width	107"
Track Construction	Caterpillar® brand D6 and 325 components with Bonfiglioli 713 Final Drives.
Track Pads	Standard 24" double bar Optional 28" double bar Optional 32" or 36" triple bar
Certification	ROPS/FOPS/OPS
Cab	Excellent visibility and comfort with 1/2" Lexan® Marguard windows. AM/FM/CD Radio. Dual joystick control Air suspended seat. Analogue and digital displays. Heat/AC. Windshield wiper. Tilt-out rear window.
Mulcher	Fecon BH350 with hydraulic trap door, hydraulic tilting push bar, and adjustable skid shoes.



FECON FTX440 ADVANTAGES

- Delivers maximum power to the mulcher through a PTO driveline protected with a fluid coupler
- Engine rpm is reduced through an industrial gear box to achieve optimal rotor torque at the mulcher under maximum loads
- Patented synchronized interface between the mulcher and crawler allows full range of motion through lift and tilt functions
- Fast and direct access to maintenance and service points by large doors, a sliding cab and a swing-out hydraulic cooler
- Comfortable Cab with User-Friendly Controls and Exterior Cab Lighting

- Operators cab must be protected with both properly maintained LEXAN® Glass (or equal) and Falling Object Protection.
 - Required LEXAN® thickness on all Skid Steers is 1/4".
 - Safety Is The Responsibility Of The Operator.
 - Specifications subject to change without notice.
- LEXAN® is a registered trademark of General Electric Company.



3460 Grant Drive
Lebanon, OH 45036
www.fecon.com
E-Mail: sales@feccon.com

Phone: 513.696.4430
Fax: 513.696.4431
Toll Free: 800.528.3113