

MORBARK® BEEVER™ M15R

BENEFITS

- Ideal for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities, this high-capacity, high-production chipper includes more standard features than any other chipper in its class.
- The powerful TorqMax™ dual feed wheel compression system generates more than 6,600 lb./ft. of material pulling force.
- Unit is pre-plumbed and outfitted for the easy installation of most aftermarket components.
- Ergonomic infeed design provides consistent feed control bar activation.
- Like all Morbark equipment, the M15R is a long-lasting, durable machine backed by a world-class parts and service support team.



Drum

30" diameter four-knife staggered-knife-pocket drum with patented removable knife holders provides maximum chipping efficiency.



Channel Frame

The 8.2 lb., 6" channel frame rails with 2" x 6" tubular steel frame with cross bracing increases structural strength while maintaining low unit weight.



Reversing Auto-feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.



Hydraulic Down Pressure

The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 4,500 lbs. of perpetual down pressure.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/25/16

General

Chipping capacity	15"
Height	8'11"
Width	7'3"
Length	18'1"
Gross weight (approximate)	8,900 lbs.
Suspension	9,000 lb. Torflex
Infeed opening	56" wide x 37" high
Throat opening	20 1/2" wide x 18" high
Drum	23 3/4" wide x 30" diameter
Engines	CAT, GM, or Perkins
Horsepower	130–174 HP
Fuel capacity	32 gallons
Hydraulic capacity	12 gallons
Frame	8.2 lb., 6" channel
Tires	(2) 215/75R17 1/2"
Hitch	2 1/2" Pintle Ring

Equipment Highlights

Dual horizontal feed wheels with TorqMax top feed wheel compression system, hydraulic lift assist, Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and direct-drive bottom feed wheel with torque arm coupler

Live hydraulic system including: ball valve, pump, motor, and valve bank with additional pre-plumbed valve section for installation of an aftermarket winch package

3" x 5" tubular steel telescoping drawbar with two 12" extensions

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

- ChipSafe® Operator Safety Shield
- Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
- Bottom Bump Bar
- Hydraulic Swivel Discharge
- Cone Holder
- Spare Tire/Mount
- Folding Infeed Tray
- Flow Control
- Axle Options Available
- Fender Options Available
- Battery Box Options Available