

MORBARK® BEEVER™ M15R TRACK



BENEFITS

- Ideal for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities, this high-capacity, high-production chipper includes more standard features than any other chipper in its class.
- The powerful TorqMax™ dual feed wheel compression system generates more than 6,600 lb./ft. of material pulling force.
- Unit is pre-plumbed and outfitted for the easy installation of most aftermarket components.
- Ergonomic infeed design provides consistent feed control bar activation.
- Like all Morbark equipment, the M15R is a long-lasting, durable machine backed by a world-class parts and service support team.



Drum

30" diameter four-knife staggered-knife-pocket drum with patented removable knife holders provides maximum chipping efficiency.



Track Undercarriage

Take the chipper to the material with 400mm rubber tracks, 4.84 PSI ground pressure, low-speed and high-speed travel ranges of 1.0 MPH and 1.8 MPH.



Reversing Autofeed

The reversing autofeed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.



Variable Force™ Hydraulic Down Pressure

The Variable Force Hydraulic Down Pressure System eliminates the use of springs and creates up to 4,500 lbs. of perpetual down pressure.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/25/16

General

Chipping capacity	15"
Height	8'6"
Width	7'10"
Length	16'
Gross weight (approximate)	13,500 lbs.
Infeed opening	56" wide x 37" high
Throat opening	20½" wide x 15" high
Drum	23¾" wide x 30" diameter
Engine	CAT or Perkins
Horsepower	147–174 HP
Fuel capacity	32 gallons
Hydraulic capacity	26 gallons
Frame	6" x 2" x ¼" wall tube
Tracks	Rubber Track Undercarriage

Equipment Highlights

Wireless Remote Control operation with tethered back-up system controls the track functions, feed functions, yoke functions and throttle functions with emergency engine stop

Dual horizontal feed wheel compression system with hydraulic lift assist, hydraulic down pressure and manually applied hydraulic down pressure at the valve handle

Reversing automatic feed system

Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment

Fuel tank sight gauge, drain plug and shut-off valve

Hydraulic tank shut-off valve, drain plug and clean-out cover

Live hydraulics; ball valve, pump, motor, control valve and variable speed flow control

Additional Features

Steel guard enclosing valve bank and automatic feed system components

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

- ChipSafe® Operator Safety Shield
- Custom paint and logo packages
- Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
- Bottom Bump Bar
- Hydraulic Swivel Discharge Chute
- Folding Infeed Tray
- Flow Control
- Battery Box Options Available