

MORBARK® BEEVER™ M15RX



BENEFITS

- With its high capacity and lighter weight design, this compact chipper is the ideal unit for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- Hydra-Lift top feed wheel compression system with spring-assisted down pressure provides more than 1,500 lbs. of material crushing power.
- Like all Morbark equipment, the M15RX is a long-lasting, durable machine backed by a world-class parts and service support team.



TorqMax™ Feed System

The powerful TorqMax™ top feed wheel compression system generates more than 3,400 lb./ft. of material pulling force.



Infeed System

The wide infeed opening with 18" diameter single top feed wheel and straight flow-through infeed easily climbs over material, reduces drag and increases chipping efficiency.



Channel Frame

The 8.2 lb., 6" channel frame rails with 2" x 6" tubular steel frame with cross bracing increases structural strength while maintaining low unit weight.



360° Swivel Discharge

360° manual crank swivel discharge with adjustable height puts chips right where they're needed without removing the Beaver from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/25/16

General

Chipping capacity	15"
Height	8'10"
Width	6'11"
Length	16'5"
Weight (approximate)	7,200 lbs.
Suspension	7,000 lb. Torflex
Infeed opening	55 1/2" wide x 34" high
Throat opening	20 1/2" wide x 16" high
Drum	23 3/4" wide x 21 3/8" diameter
Engine	CAT, GM, or Perkins
Horsepower	122.5–147 HP
Fuel capacity	32 gallons
Hydraulic capacity	13 gallons
Frame	8.2 lb., 6" channel
Tires	(2) 215/75R17 1/2"
Hitch	2 1/2" Pintle Ring

Equipment Highlights

23 3/4" wide x 21 3/8" diameter, two dual-edged knife staggered-pocket drum with dual-sided, chambered air impeller system

Single (top) horizontal feed wheel with TorqMax top feed wheel compression system, hydraulic lift assist, spring-assisted down pressure and manually applied hydraulic down pressure at the valve handle

Reversing automatic feed system

Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment

Fuel tank sight gauge and shut-off valve

Hydraulic tank shut-off valve, drain plug and clean-out cover

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield

Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard

Custom paint and logo packages

Bottom Bump Bar

Hydraulic Swivel Discharge

Cone Holder

Spare Tire/Mount

Folding Infeed Tray

Bottom Feedwheel

Flow Control

Axle, Fender and Battery Box Options Available