

MORBARK® BEEVER™ M20R FORESTRY

FEATURES

- » TorqMax Plus compression system, hydraulic lift assist, Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and sprocket driven bottom feed wheel
- » Directional flow discharge system with horizontal and vertical hydraulic positioning manufactured from abrasion resistant steel
- » Hydraulic front and dual rear stabilizers
- » 36" (91.44 cm) diameter x 33 3/8" (84.77 cm) wide drum with front pocket and six Babbitt-style knives with removable knife holders
- » Discharge clean out door on bottom
- » Steel guard enclosing valve bank and automatic feed system components
- » Live hydraulic system including: ball valve, pump, motor, and valve bank
- » Spanish and English safety decals

OTHER SPECIFICATIONS

- » Drum diameter: 36" (91.44 cm)
- » Drum width: 33 3/8" (84.77 cm)
- » Infeed Opening: 65" wide x 43" high (165 cm x 109.22 cm)
- » Throat Opening: 28" wide x 20" high (71.12 cm x 50.8 cm)
- » Frame: 2" x 10" tubular (5.08 cm x 25.4 cm)

OPTIONS


- » 4" x 4" (10.16 cm x 10.16 cm) grate system
- » Forestry, rotating or top load discharge
- » Grate System
- » Custom paint and logo packages
- » Electronic fuel gauge
- » Variable speed flow control
- » Tracks



A 6' (1.83 m) infeed bed with live WDH-110 chain drive

Advantage 3™ Drum creates more uniform chips

Remote Control



SPECIFICATIONS

US

METRIC

Chipping Capacity	20"	50.8 cm
Length	26'8"	8.12 m
Height	10'10"	3.3 m
Width	7'8"	2.34 m
Gross Weight (approx.)	18,000 lbs	8,165 kg
Suspension (Torsion)	20,000 lbs	9,071 kg
Tandem Axle	36,000 lbs leaf spring suspension	
Engine	CAT	
Horsepower	350 to 400 HP	260 to 300 kW
Fuel Capacity (tank)	65 gallons	246 litres
Hydraulic Oil	52 gallons	197 litres
Tires	(4) 235/75x17 1/2" super singles	
Hitch	3" Pintle	7.62 cm Pintle



MORBARK®

www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

2/15/17