

MORBARK® BEEVER™ M8D

BENEFITS

- Perfect for rental yards, landscapers, golf courses and pruning crews, this high-capacity unit is easy to transport and operate.
- The only chipper in its class to combine both a wide infeed chute opening and 1 ¼" thick chipping disc, the M8D has a 251-pound disc and shaft weight provides more inertia to power through material and continuously feed material.
- With a single top feed wheel compression system and 32.3 ci hydraulic motor with spring-assisted down pressure, the M8D generates more than 2,300 lb/ft of material pulling force and approximately 1,000 lb/ft of combined down pressure to easily feed a variety of materials.
- Like all Morbark equipment, the M8D is a long-lasting, durable machine backed by a world-class parts and service support team.



Belt Drive

Direct drive with belt power transfer eliminates clutch components and over center belt tensioning systems, reducing problem areas and easing maintenance burdens.




Infeed Chute

Infeed chute with 96-square-inch throat opening allows for easy material feeding and reduced trim labor and folds to reduce transport and storage length.



360° Swivel Discharge

360° swivel discharge with adjustable chip deflector puts chips right where they're needed without removing the Beever from the tow vehicle.



Feed System

A top feed wheel compression system with spring-assisted down pressure easily breaks down a variety of materials.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/25/16

General

Chipping capacity 8"
 Height 7'4"
 Width 5'3"
 Length (transport) 12'
 Length (operating) 13'10"
 Gross weight (approximate) 2,500 lbs.
 Suspension 2,500 lb. Torflex
 Infeed opening 33 ½" wide x 24 ½" high
 Throat opening 12" wide x 8" high
 Feed wheel 11 ½" wide x 9" diameter
 Disc dimensions 1 ¼" thick x 28" diameter
 Engine Kubota or Kohler
 Horsepower 35–44 HP
 Fuel capacity 10 gallons
 Hydraulic capacity 10 gallons
 Frame 2" x 4" Tubular
 Tires (2) 185/75R14 – 8-ply
 Hitch 2" Ball

Equipment Highlights

Direct drive with belt power transfer
 Automatic feed system
 Chipper disc with two 10 ½" x 4" x ⅜"
 dual-edged chipper knives and four full-length,
 bolt-on, chip-throwing paddles
 Reversible feed works control bar and dual safety
 cables located within infeed chute
 Pinned chipper hood access with integrated hood
 safety device to disconnect the start system when
 the chipper hood is opened and allow ease of
 disc maintenance.
 3" x 4" tubular steel fixed-length drawbar and
 ⅜" thick safety chains with clasp hooks
 Morthane Paint System: A chemically cured,
 electrostatically applied urethane coating with
 high-gloss finish, built-in UV protection, chip and
 chemical resistance and corrosion protection

Additional Features

Fuel tank sight gauge, drain plug and
 shut-off valve
 Hydraulic tank shut-off valve, drain plug,
 clean-out cover and vented filter head assembly
 with dipstick to check oil level
 8D, 1400 CCA Battery

Options Include

ChipSafe® Operator Safety Shield
 Variable speed flow control
 2,500 lb. Torflex suspension axle with electric
 brake system, electric brake actuator and 185R14
 tires with rims
 Custom paint and logo packages
 Knife saver tool
 Engine stop on infeed
 Material pushing tool
 Spanish and English safety decals