

# MORBARK® BEEVER™ M20R WITH INFEEED BED

## BENEFITS

- Ideal for entry-level biomass production, lot and land clearing contractors, contractors and large tree services, this high-capacity, high-production chipper has more standard features than any other chipper in its class and is offered in a variety of configurations for incredible versatility.
- The powerful TorqMax™ Plus dual feed wheel compression system generates more than 10,000 ft.lb. of material pulling force.
- The dual-sided, chambered air impeller system increases chip throwing velocity and aids in discharging light, leafy material.
- Variable Force™ Hydraulic Down Pressure System creates up to 10,000 lbs. of perpetual down pressure.
- Like all Morbark equipment, the M20R is a long-lasting, durable machine backed by a world-class parts and service support team.



### Infeed Bed

5' live rigid infeed deck with rear support drop legs and two strands of WDH-110 welded flight chain to assist in carrying material to the feed system.



### Drum

The 29 1/8" wide x 36" diameter, six-knife staggered-pocket drum with patented removable knife holders increases chipping capacity.



### Pivot Assembly

Bearing-style pivot assembly contours the radius of the drum, increases down pressure efficiency and reduces feed wheel dead space.



### Reversing Auto-feed

The reversing auto-feed system with Auto Sense™ controller briefly backs material away from the drum for reduced wear and optimum engine performance while chipping.

## SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/30/14

### General

Chipping capacity . . . . . 20"  
 Height . . . . . 11'10"  
 Width . . . . . 7'9"  
 Length . . . . . 24'9"  
 Gross weight (approximate) . . . . . 16,800 lbs.  
 Suspension . . . . . (2) 10,000 lb. torsion  
 Infeed opening . . . . . 65" wide x 43" high  
 Throat opening . . . . . 28 1/2" wide x 22" high  
 Drum . . . . . 29 1/8" wide x 36" diameter  
 Engine . . . . . CAT, Cummins or John Deere  
 Horsepower . . . . . 325–400 HP  
 Fuel capacity . . . . . 65 gallons  
 Hydraulic capacity . . . . . 43 gallons  
 Frame . . . . . 2" x 8" tubular  
 Tires . . . . . (4) 235/75x17 1/2"  
 Hitch . . . . . 3" Pintle

### Equipment Highlights

Wireless Remote Control operation with tethered back-up system controls the feed functions, yoke functions, throttle functions, rear stabilizers and hydraulic swivel discharge  
 TorqMax Plus top feed wheel compression system, hydraulic lift assist, Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and sprocket driven bottom feed wheel  
 360° height-adjustable, hydraulic swivel discharge chute with chip deflectors  
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment  
 Discharge clean-out door on bottom  
 Hydraulic front and dual rear stabilizers

### Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

### Options Include

Wireless Remote Control operation with tethered back-up system  
 Variable speed flow control  
 Skidder attachment mounted on drawbar  
 Spark arrestor muffler  
 Spare tire and rim  
 Chocks and chock holders (complete set)  
 Custom paint and logo packages  
 Knife saver tool  
 Engine stop on infeed  
 Spanish and English safety decals



**MORBARK®**  
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042  
 989.866.2381  
 www.morbark.com

PO Box 1000  
 8507 S. Winn Rd.  
 Winn, MI 48896