

C260 FORESTRY MULCHER



SPECIFICATIONS

	C260	
	U.S.	Metric
Weight with Winch & Mulcher	26,495 lb	12,018 kg
Length with Winch & Mulcher	245"	622.3 cm
Height	120"	304 cm
Width	96.25"	244 cm
Engine	260 hp Cummins	194 kW Cummins
Fuel	95 gal	359 L
Hydraulic Tank	25 gal	94 L
Track Shoe	24" Single Grouser	600 mm Single Grouser
Hydraulic System	109 gpm @ 5,070 PSI High Flow	413 L @ 34,956 kPa High Flow
Travel Speed High	3.6 mph	5.8 km/h
Travel Speed Low	1.8 mph	2.9 km/h
Cab Certification Meets	ROPS ISO 8082	ROPS ISO 8082
	FOPS ISO 8083	FOPS ISO 8083
	OPS ISO 8084/WCB G603	OPS ISO 8084/WCB G603

PREDATOR MULCHER HEADS

	U.S.	Metric
FM260-7R - Standard C260		
Weight	4,295 lb	1,948 kg
Overall Width	93.125"	236 cm
Cutting Width	77.5"	196 cm
Max Mowing Height	43"	109 cm
Cutter Teeth	Carbide Tipped	Carbide Tipped
Cutter Teeth Quantity	42	42
Ground Pressure with Winch & Mulcher	4.86 psi with Standard 24" Track	33.5 kPa with Standard 24" Track
FM260-8R - Optional C260		
Weight	5,200 lb	2,259 kg
Overall Width	106.625"	271 cm
Cutting Width	90.25"	230 cm
Max Mowing Height	43"	109 cm
Cutter Teeth	Carbide Tipped	Carbide Tipped
Cutter Teeth Quantity	46	46
Ground Pressure with Winch & Mulcher	5.02 psi with Standard 24" Track	34.6 kPa with Standard 24" Track

Rayco's C260 Crawler is a mid-sized mulcher that delivers 260 hp in a compact, low ground pressure package. A powerful Cummins QSB6.7L turbo diesel engine powers the C260. Rayco's exclusive elevated cooling design keeps engine and hydraulic temperatures within their limits in the harshest of environments. A reversing fan can be activated from the cab to clear the limbriser debris screens.

The cabs are climate controlled and sealed from dust. Operators appreciate the high-backed, heated seat with adjustable armrests and air-ride suspension. For safety, the cab is certified to meet ROPS, FOPS, and OPS specifications and is equipped with a roof-top escape hatch. LED lighting facing front, sides and rearward. A backup camera enhances rearward visibility.

The heavy-duty steel undercarriage and powerful final drives allow operators to tackle difficult terrain with confidence. The standard, 24-inch track shoes yield ground pressure of 4.86 psi (including Predator mulcher head), while the optional 28-inch shoes achieve as little as 4.16 psi. Predator mulcher heads feature variable displacement motors and will accept a variety of tooth options.



Hydraulic Tilt Cab For Easy Access to Engine and Hydraulic Components



Forestry Cab with Rooftop Escape Hatch and Heated, Suspension Seat



Predator Mulcher with Dual Variable Displacement Motors



Heavy Duty Undercarriage with 2-Speed Final Drives

800.392.2686

RAYCOMFG.COM