

# RG45X & RG45X-R SUPER Jr



Turbo diesel power, 4 wheel drive, and a hydraulic backfill blade. And it comes in a self-propelled package that fits through a 36-inch gate. The RG45X Super Jr puts together all the features customers want and fits them into a compact diesel stump cutter. Operators appreciate the large cutting dimensions as well as visibility and protection of the swing-out control station. For travel through gates, the control station swings in line. Wide floatation tires and 4-wheel drive allow the RG45X to maintain traction in challenging conditions. A hydraulic backfill blade saves time during clean up, letting you get on to the next job. Also available with wireless remote controls (RG45X-R).

## SPECIFICATIONS

RG45X & RG45X-R		
GENERAL	US	Metric
Weight	2,710 lb	1,229 kg
Length (Maximum)	121 1/2"	308.6 cm
Height	72.625" - operators shield 60" - air filter	184.5 cm 152.4 cm
Width	35 1/2"	90.2 cm
Width with Dual Wheels (Maximum)	53"	134.62 cm
Ground Clearance		
Ground Drive	4-wheel drive, 2-speed	4-wheel drive, 2-speed
Tires	18 x 8.5-10 R4 4 ply Rear - (4), Front - (2)	18 x 8.5-10 R4 4 ply Rear - (4), Front - (2)
Backfill Blade	Standard	
Wireless Remote Controls	Model RG45X-R	Model RG45X-R
ENGINE		
Model	Kubota V1505-T-E3B, Tier 4i	Kubota V1505-T-E3B, Tier 4i
Gross HP	44 hp @ 3000 RPM	32.81 kw @ 3000 RPM
Maximum Rated Torque	87 ft-lb @2000 RPM	117.96 N-m
Fuel Tank Capacity	8.5 gal	32.2 L
Electrical System	12 volts/40 AMP alternator	12 volts/40 AMP alternator
HYDRAULIC SYSTEM		
Oil Tank Capacity	2 gal	7.6 L
CUTTING WHEEL		
Wheel Diameter	20"	51 cm
Wheel Thickness	1-1/2"	3.8 cm
Cutting Wheel Bearings	1 3/4" pillow block	4.45 cm pillow block
Cutting Teeth	Rayco Super Tooth™	Rayco Super Tooth™
Cutter Teeth Quantity	24	24
Cutter Wheel Engagement	Electromagnetic clutch with the "quick stop" brake system	Electromagnetic clutch with the "quick stop" brake system
CUTTING RANGE WITHOUT REPOSITIONING		
Below Ground Level	14"	35.6 cm
Above Ground Level	24.5"	62.2 cm
Cutting Width	60"	152 cm



Available with Radio Remote Controls (RG45X-R)



Dual Rear Wheels for Increased Stability and Traction



Kubota 44 hp Diesel Engine

# RG45 TRAC Jr



The RG45 Trac Jr offers its user the ultimate in versatility and performance in a mid-sized stump cutter. Excellent cutting power, radio remote controls, a hydraulic backfill blade, and expandable rubber tracks mean the RG45 Trac Jr can get to almost any stump and remove it quickly. The extendable, rubber track undercarriage provides a stable, 50-inch wide stance for cutting, while retracting to 35-inches to squeeze through backyard gates. The long track base ensures stability and lowers ground pressure to tread lightly on delicate lawns. Non-marking tracks are available. The reliable, Kubota 44hp diesel engine provides plenty of muscle to tackle large stumps. When it's time to clean up, the hydraulic backfill blade easily pushes chips and soil to avoid raking.

## SPECIFICATIONS

RG45 Trac Jr		
GENERAL	US	Metric
Weight	3,260 lb	1,479 kg
Length (Maximum)	144"	366 cm
Height	73" - Operators Shield 61" - Air Filter	185.4 cm 155 cm
Width	50" Expanded 35" Retracted	127 cm 89 cm
Tracks	Rubber	Rubber
Backfill Blade	Standard 50" Expanded 35" Retracted	Standard 50" Expanded 35" Retracted
Wireless Remote Controls	Standard	Standard
ENGINE		
Model	Kubota V1505-T-E3B, Tier 4i	Kubota V1505-T-E3B, Tier 4i
Gross HP	44 hp @ 3000 RPM	32.81 kw @ 3000 RPM
Maximum Rated Torque	87 ft-lb @2000 RPM	117.96 N-m
Fuel Tank Capacity	8.5 gal	32.2 L
Electrical System	12 volts/40 AMP alternator	12 volts/40 AMP alternator
HYDRAULIC SYSTEM		
Oil Tank Capacity	1.5 gal	5.7 L
CUTTING WHEEL		
Wheel Diameter	20"	51 cm
Wheel Thickness	1-1/2"	3.8 cm
Cutting Wheel Bearings	1 3/4" pillow block	4.45 cm pillow block
Cutting Teeth	Rayco Super Tooth™	Rayco Super Tooth™
Cutter Teeth Quantity	24	24
Cutter Wheel Engagement	Electromagnetic clutch with the "quick stop" brake system	Electromagnetic clutch with the "quick stop" brake system
CUTTING RANGE WITHOUT REPOSITIONING		
Below Ground Level	14"	35.6 cm
Above Ground Level	24.5"	62.2 cm
Cutting Width	60"	152 cm



Radio Remote Controls



Extendable Rubber Tracks



Standard Hydraulic Backfill Blade