

Rayco's T360 mulcher offers all the right features in a highly productive package to suit your large-mulcher needs. The T360 is powered by a 360 hp Cummins QSM11 engine that produces peak power of 385 hp and 1350 pound-foot of torque. A closed loop hydrostatic system delivers power to the Predator mulcher or Hydra-Stumper cutter head. A patent-pending, elevated cooling box in the limbriser houses engine and hydraulic system radiators, in addition to the engine radiator in the rear of the engine compartment. This Rayco-exclusive design maximizes cooling capacity and debris screening.

Inside the cab, the operator is kept comfortable in the fully-sealed and climate controlled cab. The T360 cabin hosts creature comforts such as a high-backed suspension seat and pilot joystick controls. Safety is built into the T360's cab with standard ROPS, FOPS, and OPS certifications as well as a rooftop escape hatch. Onboard diagnostic and monitoring information is provided through a color LCD panel, allowing the operator to track numerous aspects of machine operation and performance. A backup camera is standard to increase rearward visibility.

Heavy duty track chain will accommodate track shoe widths from 24 to 30-inches wide.



T360 with Hydra Stumper Stump Cutter Head



Rayco Exclusive Elevated Cooling System




Power for Large Scale Clearing



Tilt Cab for Access to Hydraulic Components





T360 FORESTRY MACHINE

SPECIFICATIONS

Weight of Carrier with Winch 33,200 lb 15,069 kg Overall Length of Carrier 183* 465 cm Height 127* 322 cm Ground Clearance 22* at Bally - 17* at Winch 50 cm at Bally - 43 cm at Winch Overall Width of Carrier 112* 284 cm Full Capacity 182 gal 500 L Hydraulic Winch Rear Mounted, 35K lb Capacity Rear Mounted, 35K lb Capacity ENGINE Winch Rear Mounted, 35K lb Capacity Rear Mounted, 35K lb Capacity Beak HP 360 hp @ 2,100 rpm 268 kW Mode! Rated HP 385 hp @ 1,800 rpm 287 kW Weight USDEPCARRIAGE Track Shoes 28* Double Grouser, Steel 700 mm Double Grouser, Steel TRAYEL SPEED Track Shoes 3.7 mph 3.22 km/h 3.22 km/h FM360-9 PREDATOR MULCHER HEAD 3.22 km/h 3.22 km/h 3.22 km/h Weight 7,200 lb 3.28 kB 6.85 cm 6.85 cm Overall Width 112* 28.45 cm 6.85 cm 6.85 cm Group Pressure with Winch an	SPECIFICATIONS		
General Carrier with Winch 33,200 lb 15,059 kg Worght of Carrier with Winch 33,200 lb 15,059 kg Overall Leight of Carrier 183¹ 485 cm Height 122° 322 cm 322 cm Ground Clearance 2² st Belly 17° st Winch 56 cm at Belly -43 cm at Winch Overall Width of Carrier 112° 284 cm 284 cm Fuel Capacity 132 gal 500 L 32 km Mounted, 35K ib Capacity 284 cm 4 cm Fuel Capacity 132 gal 500 L 32 km Mounted, 35K ib Capacity 284 cm 4 cm 4 cm Model Cummins QSM 11L, Tier 3/Stago 3 Cummins QSM 11L, Tier 3/Stago 3 Cummins QSM 11L, Tier 3/Stago 3 287 kW 4 cm		T360	
Weight of Carrier with Winch 33,200 lb 15,069 kg Overall Length of Carrier 183* 465 cm Height 127* 322 cm Ground Clearance 22* at Bally - 17* at Winch 50 cm at Bally - 43 cm at Winch Overall Width of Carrier 112* 284 cm Full Capacity 182 gal 500 L Hydraulic Winch Rear Mounted, 35K lb Capacity Rear Mounted, 35K lb Capacity ENGINE Winch Rear Mounted, 35K lb Capacity Rear Mounted, 35K lb Capacity Beak HP 360 hp @ 2,100 rpm 268 kW Mode! Rated HP 385 hp @ 1,800 rpm 287 kW Weight USDEPCARRIAGE Track Shoes 28* Double Grouser, Steel 700 mm Double Grouser, Steel TRAYEL SPEED Track Shoes 3.7 mph 3.22 km/h 3.22 km/h FM360-9 PREDATOR MULCHER HEAD 3.22 km/h 3.22 km/h 3.22 km/h Weight 7,200 lb 3.28 kB 6.85 cm 6.85 cm Overall Width 112* 28.45 cm 6.85 cm 6.85 cm Group Pressure with Winch an		U.S.	Metric
Overall Length of Carrier 183° 465 cm Height 127° 322 cm Ground Clearance 22" at Belly - 17" at Winch 56 cm at Belly - 43 cm at Winch Overall Width of Carrier 112" 284 cm Fuel Capacity 132 gal 500 L Hydraulic Winch Rear Mounted, 35K lb Capacity 600 L Hydraulic Winch Cummins OSM 11L, Tier 3/Stage 3 Cummins OSM 11L, Tier 3/Stage 3 Reated HP 360 hg @ 2,100 rpm 268 kW Peak HP 385 hg @ 1,800 rpm 287 kW UNDERCARRIAGE 28" Double Grouser, Steel 700 mm Double Grouser, Steel Track Shoses 28" Double Grouser, Steel 700 mm Double Grouser, Steel TRABYEL SPED 75.00 lb 3,22 km/h High Range 3,7 mph 5,95 km/h Low Range 7,200 lb 3,256 kg Overall Width 112" 245 km Overall Width 112" 284 b cm Cutting Width 91.25" 85.5 cm Teeth (44 + 2) FAE Single Bolt Type C & C\SD Teeth (44 + 2) FAE Single Bolt Type C & C\SD	GENERAL		
Height Ground Clearance 22° at Belly - 17" at Winch 66 cm at Belly - 43 cm at Winch 67 cm at Belly -43 cm at Winch 67 cm at Belly	Weight of Carrier with Winch	33,200 lb	15,059 kg
Ground Clearance 22° at Belly - 17° at Winch 56 cm at Belly - 43 cm at Winch Coveral Width of Carrier 112° 284 cm 500 L 112° 284 cm 500 L 112° 300 L 30	Overall Length of Carrier	183"	465 cm
Overall Wildth of Carrier 112* 284 cm Fuel Capacity 132 gal 500 L Hydraulic Winch Rear Mounted, 58K lb Capacity Rear Mounted, 35K lb Capacity ENGINE Whole Image: Season of Sea	Height	127"	322 cm
Fuel Capacity 132 gal 500 L Hydraulic Winch Rear Mounted, 35K ib Capacity Rear Mounted, 35K ib	Ground Clearance	22" at Belly - 17" at Winch	56 cm at Belly - 43 cm at Winch
Hydraulic Winch Rear Mounted, 35K lb Capacity Rear Mounted, 35K lb Capacity ENGINE Unminis QSM 11L, Tier 3/Stage 3 Cummins QSM 11L, Tier 3/Stage 3 Rated HP 360 hp @ 2,100 rpm 268 kW Peak HP 385 hp @ 1,800 rpm 287 kW UNDERCARIAGE Track Shoes 28* Double Grouser, Steel 700 mm Double Grouser, Steel TRAVEL SPED Track Shoes 3.7 mph 5.95 km/h Low Range 3.0 mph 3.266 kg 3.22 km/h FMS30-9 SPEDATOR MULCHER HEAD Track Shoes 3.266 kg 3.266 kg Overall Width 112" 284.5 cm 3.260 kg	Overall Width of Carrier	112"	284 cm
### A Part	Fuel Capacity	132 gal	500 L
Model Cummins QSM 11L, Tier 3/Stage 3 Cummins QSM 11L, Tier 3/Stage 3 Rated HP 360 hp @ 2,100 rpm 268 kW Peak HP 385 hp @ 1,800 rpm 287 kW UNIDERCARRIAGE Track Shoes 28" Double Grouser, Steel 700 mm Double Grouser, Steel TRAVEL SPEED High Range 3.7 mph 5.95 km/h Low Range 2.0 mph 3.22 km/h FMB50-3 PREDATOR MULCHER HEAD V Weight 7,200 lb 3,286 kg Overall Width 112" 284.5 cm Cutting Width 91.25" 232 cm Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth Orive Motors (2) Variable Displacement (3) x kPa Cessor Pypra-StUMPER CUTTER Heat 48" 122 cm Wheel Diameter 48" 2.6 cm Cutter Wheel Bearings 3-7 inc Plaimeter Pillow Block 8.7 cm Cutting Teeth 48 companies Pillow Block 8.7 cm Cutting Range 8 lo	Hydraulic Winch	Rear Mounted, 35K lb Capacity	Rear Mounted, 35K lb Capacity
Rated HP 360 hp @ 2,100 rpm 268 kW Peak HP 385 hp @ 1,800 rpm 287 kW UNDERCARRIAGE Track Shoes 28" Double Grouser, Steel 700 mm Double Grouser, Steel TRAVEL SPEED High Range 3.7 mph 5.95 km/h Low Range 2.0 mph 3.22 km/h FM850-3 PREDATOR MULCHER HEAD Weight 7,200 lb 3,266 kg Overall Width 112" 284.5 cm Cutting Width 91.25" 232 cm Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth Drive Motors (2) Variable Displacement 37.3 kPa CB350 HYDRA-STUMPER CUTTER Head 48" 122 cm Wheel Thickness 3" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutter Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 8" 10" 2,7 m Cut	ENGINE		
Peak HP 385 hp @ 1,800 rpm 287 kW UNDERCARRIAGE Track Shoes 28° Double Grouser, Steel 700 mm Double Grouser, Steel TRAVEL SPEED TRAVEL SPEED 5.95 km/h Low Range 2.0 mph 3.22 km/h Low Range 2.0 mph 3.22 km/h FM350-8 PREDATOR MULCHER HEAD 2.0 mph 3.266 kg Weight 7,200 lb 3,266 kg Overall Width 112" 284.5 cm Cutting Width 91.25" 292 cm Rotor Diameter 27" 88.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth Drive Motors (2) variable Displacement (2) Variable Displacement Ground Pressure with Winch and Mulcher 5.41 psi 37.3 kPa CB350 HYDRA-STUMPER CUTTER Heat Wheel Diameter 48" 122 cm Wheel Diameter 48" 3" 7.6 cm Cutting Teeth Rayco Monster Tooth™ Rayco Monster Tooth™ Rayco Monster Tooth™ Cutting Range 56 56	Model	Cummins QSM 11L, Tier 3/Stage 3	Cummins QSM 11L, Tier 3/Stage 3
UNDERCARRIAGE Track Shoes 28" Double Grouser, Steel 700 mm Double Grouse	Rated HP	360 hp @ 2,100 rpm	268 kW
Track Shoes 28" Double Grouser, Steel 700 mm Double Grouser, Steel TRAVEL SPEED High Range 3.7 mph 5.95 km/h Low Range 2.0 mph 3.22 km/h FM360-8 PREDATOR MULCHER HEAD Weight 7,200 lb 3,266 kg Overall Width 112" 284.5 cm Cutting Width 91.25" 232 cm Rotor Diameter 27" 68.5 cm Teeth (44 + 2) FAE Single Bolt Type C & C\SD Teeth (44 + 2) FAE Single Bolt Type C & C\SD Teeth Drive Motors (2) Variable Displacement (2) Variable Displacement Ground Pressure with Winch and Mulcher 5.41 psi 37.3 kPa CB360 HYDRA-STUMPER CUTTER Head Wheel Diameter 48" 122 cm Wheel Thickness 3" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutter Teeth Quantity 56 56 Weight 500 lb 2,950 kg Cutting Range 8elow Ground Level 8'10" 2.7 m Cutting W	Peak HP	385 hp @ 1,800 rpm	287 kW
High Range 3.7 mph 5.95 km/h Low Range 2.0 mph 3.22 km/h FML8GO-S PREDATOR MULCHER HEAD Weight 7,200 lb 3,266 kg Overall Width 112° 284.5 cm Cutting Width 91,25° 232 cm Rotor Diameter 27° 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (2) Variable Displacement (2) Variable Displacement (2) Variable Displacement (3) x3.8 kp Ground Pressure with Winch and Mulcher 5.41 psi 37.3 kPa Teeth 48° 48° 122 cm Wheel Diameter 48° 5.41 psi 37.3 kPa Teeth 122 cm Wheel Diameter 48° 7.6 cm Cutter Wheel Bearings 3° 7.16° Diameter Pillow Block 8.7 cm Cutter Wheel Bearings 3-7/16° Diameter Pillow Block 8.7 cm Cutter Teeth Quantity 56 56 56 Cutter Teeth Quantity 56 56 56 Cutting Range Below Ground Level 37° 90 50 b 2.950 kg Cutting Range Below Ground Level 81° 10° 2.7 m Cutting Width 91° 2.7 tm Cutting Width 91° 2.7 tm	UNDERCARRIAGE		
High Range	Track Shoes	28" Double Grouser, Steel	700 mm Double Grouser, Steel
Low Range 2.0 mph 3.22 km/h FM360-8 PREDATOR MULCHER HEAD FM360-8 PREDATOR MULCHER HEAD Weight 7,200 lb 3,266 kg Overall Width 112" 284.5 cm Cutting Width 91,25" 232 cm Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth Drive Motors (2) Variable Displacement (2) Variable Displacement Ground Pressure with Winch and Mulcher 5.4 t psi 37.3 kPa CB360 HYDRA-STUMPER CUTTER Head Wheel Diameter 48" 122 cm Wheel Plainings 3" 7.6 cm Cutter Wheel Bearings 3" 7.6 cm Cutting Teeth Rayco Monster Tooth™ Rayco Monster Tooth™ Cutter Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 8" 10" 2.7 m Cutting Width 9" 2.74 m	TRAVEL SPEED		
Weight 7,200 lb 3,266 kg Overall Width 112" 284,5 cm Cutting Width 91,25" 232 cm Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth Drive Motors (2) Variable Displacement (2) Variable Displacement (2) Variable Displacement (3,7,3 kPa) CB360 HYDRA-STUMPER CUTTER Head Wheel Diameter 48" 122 cm Wheel Diameter 48" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutting Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 810" 2,7 m Cutting Width 91" 2,7 m	High Range	3.7 mph	5.95 km/h
Weight 7,200 lb 3,266 kg Overall Width 112" 284.5 cm Cutting Width 91.25" 232 cm Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (2) Variable Displacement (2) Variable Displacement (2) Variable Displacement (37.8 kPa Cround Pressure with Winch and Mulcher 5.41 psi 37.8 kPa CB360 HYDRA-STUMPER CUTTER Head CWeel Diameter 48" 122 cm Wheel Diameter 48" 7.6 cm Cutter Wheel Bearings 3" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutting Teeth Quantity 56 56 Cutter Teeth Quantity 56 6,500 lb 56 Weight 6,500 lb 56 Cutting Range Cutting Range Below Ground Level 37" 94 cm Above Ground Level 91" 91" 2.74 m Cutting Width 91" 2.74 m	Low Range	2.0 mph	3.22 km/h
Overall Width 112" 284.5 cm Cutting Width 91.25" 232 cm Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth Drive Motors (2) Variable Displacement (2) Variable Displacement (2) Variable Displacement (3) Variable Displacement (3) Variable Displacement (44+2) FAE Single Bolt Type C & C\SD Teeth (44	FM360-8 PREDATOR MULCHER HEAD		
Cutting Width 91.25" 68.5 cm Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (2) Variable Displacement (2) Variable Displacement (3) AFPA CB360 HYDRA-STUMPER CUTTER Head Wheel Diameter 48" 122 cm Wheel Diameter 48" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block Cutting Teeth Rayco Monster Tooth™ Cutter Teeth Quantity 66 6,500 lb 2,950 kg Cutting Range Below Ground Level Above Ground Level 8' 10" 9' 2.74 m Cutting Width	Weight	7,200 lb	3,266 kg
Rotor Diameter 27" 68.5 cm Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth Drive Motors (2) Variable Displacement (2) Variable Displacement 37.3 kPa CB360 HYDRA-STUMPER CUTTER Head Wheel Diameter 48" 122 cm Wheel Diameter 48" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block Cutting Teeth Rayco Monster Tooth™ Rayco Monster Tooth™ Cutter Teeth Quantity 56 6,500 lb 56 Weight Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.74 m Cutting Width	Overall Width	112"	284.5 cm
Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (44+2) FAE Single Bolt Type C & C\SD Teeth (2) Variable Displacement (2) Variable Displacement 37.3 kPa CB360 HYDRA-STUMPER CUTTER Head Wheel Diameter 48" 48" 122 cm Wheel Diameter Wheel Bearings 3-7/16" Diameter Pillow Block Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutting Teeth Cutter Quantity 56 56 Weight Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 9.74 m Cutting Width 9' 2.74 m	Cutting Width	91.25"	232 cm
Drive Motors (2) Variable Displacement (2) Variable Displacement Ground Pressure with Winch and Mulcher 5.41 psi 37.3 kPa **CB360 HYDRA-STUMPER CUTTER Head* **Wheel Diameter** **Wheel Diameter** **Wheel Diameter** **Wheel Thickness* **Cutter Wheel Bearings* **Cutter Wheel Bearings* **Cutting Teeth* **Cutting Teeth* **Cutter Teeth Quantity* **End On Ib** **End On Ib** **Cutting Range** **Below Ground Level* **Above Ground Level** **Above Ground Level** **Cutting Width** **Section** **Cutting Width** **Cutting Width** **Cutting Width** **Cutting Width** **Cutting Vidth** **Cutting	Rotor Diameter	27"	68.5 cm
Ground Pressure with Winch and Mulcher CB360 HYDRA-STUMPER CUTTER Head Wheel Diameter 48" 3" 7.6 cm Wheel Thickness 3" 3-7/16" Diameter Pillow Block 8.7 cm Cutter Wheel Bearings Cutting Teeth Cutter Teeth Quantity 56 Weight 6,500 lb Cutting Range Below Ground Level Above Ground Level Above Ground Level Cutting Width 9' 37.3 kPa 42.2 cm 7.6 cm 8.7 cm 7.6 cm 8.7 cm 6.6 cm 8.7 cm 6.6 cm 8.7 cm 6.500 lb 2.950 kg Cutting Range 8.1 0" 2.7 m Cutting Width 9.1 cm 4.1 cm 4.2 cm 4.3 cm 4.3 cm 4.4 cm 4.3 cm 4.4 cm 4.5 cm 4.7 cm	Teeth	(44+2) FAE Single Bolt Type C & C\SD Teeth	(44+2) FAE Single Bolt Type C & C\SD Teeth
Wheel Diameter 48" 122 cm Wheel Thickness 3" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutting Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.74 m	Drive Motors	(2) Variable Displacement	(2) Variable Displacement
Wheel Diameter 48" 7.6 cm Wheel Thickness 3" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutting Teeth Rayco Monster Tooth™ Rayco Monster Tooth™ Rayco Monster Tooth™ Router Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	Ground Pressure with Winch and Mulcher	5.41 psi	37.3 kPa
Wheel Thickness 3" 7.6 cm Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutting Teeth Rayco Monster Tooth™ Rayco Monster Tooth™ Cutter Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	CB360 HYDRA-STUMPER CUTTER Head		
Cutter Wheel Bearings 3-7/16" Diameter Pillow Block 8.7 cm Cutting Teeth Rayco Monster Tooth™ Rayco Monster Tooth™ Cutter Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range 37" 94 cm Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	Wheel Diameter	48"	122 cm
Cutting TeethRayco Monster Tooth™Rayco Monster Tooth™Cutter Teeth Quantity5656Weight6,500 lb2,950 kgCutting RangeBelow Ground Level37"94 cmAbove Ground Level8' 10"2.7 mCutting Width9'2.74 m	Wheel Thickness	3"	7.6 cm
Cutter Teeth Quantity 56 56 Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	Cutter Wheel Bearings	3-7/16" Diameter Pillow Block	8.7 cm
Weight 6,500 lb 2,950 kg Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	Cutting Teeth	Rayco Monster Tooth™	Rayco Monster Tooth™
Cutting Range Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	Cutter Teeth Quantity	56	56
Below Ground Level 37" 94 cm Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	Weight	6,500 lb	2,950 kg
Above Ground Level 8' 10" 2.7 m Cutting Width 9' 2.74 m	Cutting Range		
Cutting Width 9' 2.74 m	Below Ground Level	37"	94 cm
•	Above Ground Level	8' 10"	2.7 m
Ground Pressure with winch and Hydra-Stumper 5.31 psi 36.6 kPa	Cutting Width	9,	2.74 m
	Ground Pressure with winch and Hydra-Stumper	5.31 psi	36.6 kPa

800.392.2686 RAYCOMFG.COM