



The DS series are rugged chain & bar dangle saws are designed for use on excavators, track feller bunchers, and loader type carriers. The grapple style arm design allows operator to handle standing or fallen timber to fell, pile, cross-cut, trim, top and shovel. This head is ideal for right-of-way clearing, selective cutting, salvaging storm timber and harvesting large trees

The DS-20 recommended for the larger high flow hydraulic skid steers and 10 - 15 ton excavators has a 3/4 pitch saw chain running on a 28" saw bar capable of cutting 20" in a single pass or cut 28" in multiple passes.

The DS-28 & DS-28C recommended for the 14 - 25 ton excavators have a 3/4 pitch saw chain running on a 37'' bar capable of cutting 28'' in a single pass or 36'' cut with multiple passes.



CHAIN SAW GRAPPLE

	DS-20	DS-28	DS-28C
Max. Opening	28"	38"	38"
Single Cut Cap.	20"	30"	30"
Saw Bar	28"	37"	37"
Saw Chain	3/4 pitch	3/4 pitch	3/4 pitch
Sprocket	9 tooth	9 tooth	9 tooth
Chain Oil Res.	8 gal	6 gal	8 gal
Rotator	Baltrotor GR16	Rotobec 252	Rotobec R6500
Motor	34cc	40cc	40cc
Weight	2400 lb	2400 lb	2800 lb
Carrier	10-15 ton	14-25 ton	14-25 ton

NOW AVAILABLE 360° CONTINUOUS ROTATION DS-28C







