


GRAPPLES

Mini



Model	Opening	Closure
4040	40" 101 cm	2" 5 cm
4252	52" 121 cm	2" 5 cm
4848	48" 121 cm	2" 5 cm
4860	60" 152 cm	2" 5 cm
6060	60" 152 cm	2" 5 cm
6072	72" 182 cm	3" 7 cm
RTG48	48" 121 cm	2" 5 cm
RTG60	60" 152 cm	2" 5 cm

Mid



Large



Optional Winch:



12,000 lb Ramsey Winch

The heavy duty by-pass RTG series tractor grapples feature side to side, front to back swivel, with a spring loaded 270° rotation which allows grapple to return to position.

Category 1, RTG-48, has a maximum working pressure of 3500 psi and 8,500 lbs of clamping force. The boom extends 42" beyond the 3 pt-hitch arms.

Category 2, RTG-60, has a maximum working pressure of 3500 psi and 14,000 lbs. of clamping force. The boom extends 55" beyond the 3 pt-hitch arms.



Category 1

3 pt hitch



Category 2

Width	Weight	Cylinder	Rotator Rating
9" 22 cm	310lbs 140 kg	2 x 7" 5 x 17 cm	2,250 lbs 1,020 kg
11" 38 cm	430 lbs 195 kg	2 x 8.75" 5 x 22 cm	6,745 lbs 3,059 kg
15" 38 cm	750 lbs 340 kg	2 x 8.75" 5 x 22 cm	6,745 lbs 3,059 kg
15" 38 cm	890 lbs 403 kg	2.5 x 10" 6 x 25 cm	6,745 lbs 3,059 kg
15" 38 cm	1080 lbs 490 kg	2.5 x 10" 6 x 25 cm	10,000 lbs 4,535 kg
15" 38 cm	1250 lbs 567 kg	3 x 12" 7 x 30 cm	10,000 lbs 4,535 kg
15" 38 cm		2 x 8.75" 5 x 22 cm	
15" 38 cm		2.5 x 10" 6 x 25 cm	

Offering a broad range of by-pass grapples for the mini carriers up to the larger skid steers, tractors and excavators. They feature the standard push bar for assisting material loading and or directional cutting. The cradle in the universal quick attach plate has serrated edges to secure the load both horizontally and vertically. The oversized rotator offers 360° continuous rotation. The heavy duty construction with oversized chrome pins and hardened steel bushings ensures a long life.

The design offers good visibility and simplicity of operating.

