

STATIONARY CHIPPERS

OPTIONS

- (6) steel chipper support legs to accommodate 60" elevation to bottom of infeed spout
- Transition piece for 48", 58", and 66" chippers to go from square discharge to round blowpipe.
- 10" - 12" round blowpipe straight pipe.
- Hydraulic telescoping swivel discharge spout. (requires auxiliary hydraulic power supply to operate)
- Hydraulic hood opener includes cylinder and lugs. Does not include hydraulic power supply to valve to operate same. (Available for 75", 83", and 96" chippers)
- Manual swivel discharge spout. (includes transition piece)
- 12" Black Blowpipe with 3/8" wall thickness bent 90 degrees. Height is 48" and length is 90"0.
- "F" wheel assembly for 75" chippers includes hydraulic drive, forward and reverse controls for drive wheels and controls to raise and lower "F" wheel assembly. (requires hydraulic power supply from another source)
- "F" wheel assembly for 83" chippers include all of the above standard equipment.
- 11.30' long spout extension to load open top rail cars, complete with legs, down spout, sliding hood and components. Requires hydraulic power supply from another source.
- 4" Thick chipper fronts
- Heavy duty fan blades with inserts
- 5" thick chipper disc



SPECIFICATIONS Note: Specifications may vary with equipment options

03052010

GENERAL

96" Chipper

Capacity30" roundwood
 Length 104"
 Weight30,000 lbs.
 Width75"
 Height.....104.5"

75" Chipper

Capacity22" roundwood
 Length83"
 Weight15,600 lbs.
 Width81"
 Height.....84"

58" Chipper

Capacity15" roundwood
 Length67"
 Weight8,200 lbs.
 Width58"
 Height.....65"

83" Chipper

Capacity27" roundwood
 Length92"
 Weight19,000 lbs.
 Width63"
 Height.....90"

66" Chipper

Capacity18" roundwood
 Length82"
 Weight11,000 lbs.
 Width68"
 Height.....74.5"

48" Chipper

Capacity15" roundwood
 Length67"
 Weight8,200 lbs.
 Width67"
 Height.....65"



800-831-0042 989-866-2381
 www.morbark.com